

# Block sensor



A surface mounting brass block, designed specifically for the plastics industry but used in other areas, which is located by a 4mm tube and is fixed into place via a bolt. Available in 2 manufacture options, Fabricated Thermocouple (FT) and Resistance Thermometer (RT).

Our standard range is shown below, although any special can be manufactured upon request.

Contact the Sales office for details and a quotation.

## Block sensor

### **Model BI01**

Operating Temperature : -60 to 350°C

Type : Thermocouple J, K or 4-wire RT

Hot junction : Grounded - Thermocouple

### General Specification

Cable type : Glass-fibre with stainless steel over-braid

Termination : 100mm flying tails

<u>Model code</u>			
Model	Calibration	Cable length (in Mtrs)	Options
BI01	J	2 (2Mtrs)	Cable type A Armour Termination Z Std plug
	K	3 (3Mtrs)	
	RT	10 (10Mtrs)	

### Accessories



Compression fittings



Connectors



Extension cable

## **Helium Projects Ltd**

Projects House,  
 Rear of 6 St Lawrence Avenue, Worthing,  
 West Sussex, BN14 7JH  
 Tel: +44(0) 1903 211121 Fax: +44(0) 1903 211130  
 email: [sales@helium.uk.net](mailto:sales@helium.uk.net)  
 Website: [www.helium.uk.net](http://www.helium.uk.net)