

# Head mounted sensor with removable insert



These are general-purpose probe assemblies with a white polypropylene head. Supplied with 6mm diameter, spring-loaded DIN disc removable insert. 316 S/S outer sheath. Also available with a stainless steel head

Our standard range is shown below, although any special can be manufactured upon request.

Contact the Sales office for details and a quotation.



## Stainless steel Head option

### Standard Temperature Fabricated

#### Model Hd22

Operating Temperature	-60 to +350°C Thermocouples -50 to +250°C Resistance Thermometer
Type	J, K, T or N 4 wire Resistance Thermometer
Hot junction	Grounded (T/C) as standard

### General Specification

Probe Diameter	12mm
Probe length	Measured from below hex
Termination	Aluminium head (IP67) with M20 electrical connection cable gland

Model code				
Model	Calibration	Probe diameter	Sensor Length (in mm)	Options
<b>Hd22</b>	J	12 (12mm)	<b>050 (50mm)</b> <b>100 (100mm)</b> <b>200 (200mm)</b>	<b>Hot Junction</b> Suffix code with I or G if not standard  <b>Termination</b> For flying tails Suffix with F  <b>Transmitter</b> TX (range)
	K			
	T			
	N			
<b>RT</b>				
<b>Duplex</b>				
<b>DHd22</b>				
<b>(3 wire Only Pt100)</b>				

### Accessories



Compression fittings



Thermowells



Extension cable

## Helium Projects Ltd

Projects House,  
Rear of 6 St Lawrence Avenue, Worthing,  
West Sussex, BN14 7JH  
Tel: +44(0) 1903 211121 Fax: +44(0) 1903 211130  
email: [sales@helium.uk.net](mailto:sales@helium.uk.net)  
Website: [www.helium.uk.net](http://www.helium.uk.net)