

Head mounted sensor with IDF fitting



These are general-purpose probe assemblies with a IDF fitting below a white polypropylene head. Supplied with 6mm diameter, spring-loaded DIN disc removable insert. 316 S/S outer sheath. Also available with a stainless steel head.

Our standard range is shown below, although any special can be manufactured upon request.

Contact the Sales office for details and a quotation.



Stainless steel Head option

Standard Temperature Fabricated

Model Hd28

Operating Temperature	-60 to +350°C Thermocouples -50 to +250°C Resistance Thermometer
Type	J, K, T or N 4 wire Resistance Thermometer
Hot junction	Grounded (T/C) as standard

General Specification

Probe Diameter	12mm
Lagging length	50mm
Probe length	Measured from below fitting
Termination	Aluminium head (IP67) with M20 electrical connection cable gland

Model code				
Model	Calibration	Sensor Length (in mm)	IDF	Options
Hd28	J			Hot Junction Suffix code with I or G if not standard Termination For flying tails Suffix with F Transmitter TX (range)
	K	050 (50mm)	1"	
	T	100 (100mm)	2"	
	N	200 (200mm)	3"	
	RT		4"	
Duplex DHd28 (3 wire Only Pt100)				

Accessories



Compression fittings



Thermowells



Extension cable

Helium Projects Ltd

Projects House,
Rear of 6 St Lawrence Avenue, Worthing,
West Sussex, BN14 7JH
Tel: +44(0) 1903 211121 Fax: +44(0) 1903 211130
email: sales@helium.uk.net
Website: www.helium.uk.net