


Twist Melt bolt sensor Thermally insulated tip

Mb05



Designed to withstand high pressure and enable direct measurement of molten material. The free running body will enable the blade style tip to be orientated, to minimize obstruction to the plastic flow, as well as allowing the bolt to be screwed into the process without twisting the cable. This 152mm/6" long bolt is available with either ½"UNF or M18x1.5 process threads and blade lengths from 0mm – 20mm.

Additional features included are a PTFE insulated behind the tip to reduce cold end effect.

Our standard range is shown below, although any special can be manufactured upon request.

Contact the Sales office for details and a quotation.

Twist Melt bolt sensor

Model Mb05

Operating Temperature : -60 to 350°C

Type : J, J DIN, K

Hot junction : Grounded as standard – Thermocouple

General Specification

Bolt length : 152mm (6")

Tip length : 0mm / 5mm / 10mm / 15mm / 20mm or 25mm

Thread type : ½"UNF – 20 or M18 x 1.5

Cable type and length : 100mm – Glass-fibre with stainless steel over-braid as standard

Termination : 2-pin standard plug (comes complete with mating socket)

Model code

Model	Calibration	Tip length (in mm)	Cable length (in Mtrs) if non standard	Options
Mb05	J JD K	0	1 (1Mtrs) 2 (2Mtrs) 5 (5Mtrs)	Termination A 100mm flying Tails Process thread M18 M18 x 1.5 I Insulated Junction WSQ 90°C cable exit
		5		
		10		
		15		
		20		
25				

Accessories



Compression fittings



Connectors



Extension cable

Helium Projects Ltd

Projects House,
Rear of 6 St Lawrence Avenue, Worthing,
West Sussex, BN14 7JH

Tel: +44(0) 1903 211121 Fax: +44(0) 1903 211130

email: sales@helium.uk.net

Website: www.helium.uk.net