

Probe sensor with IDF fitting



These are general-purpose probe assemblies with a IDF fitting, cable and terminated in flying tails. 316 S/S outer sheath.

Our standard range is shown below, although any special can be manufactured upon request.

Contact the Sales office for details and a quotation.

Standard Temperature Fabricated

Model Pr22

Operating Temperature	: -60 to +350°C Thermocouples
	: -50 to +250°C Resistance Thermometer
Type	: J, K, T or N
	: 4 wire Resistance Thermometer
Hot junction	: Grounded (T/C) as standard

General Specification

Probe Diameter	: 6mm
Lagging length	: 50mm
Probe length	: Measured from below fitting
Termination	: 100mm flying tails

Model code

Model	Calibration	Sensor Length (in mm)	IDF	Options
Pr22	J	050 (50mm) 100 (100mm) 200 (200mm)	1" 2" 3" 4"	Hot Junction Suffix code with I or G if not standard Termination For flying tails Suffix with F
	K			
	T			
	N			
RT				
Duplex				
DPr22				
(3 wire Only Pt100)				

Accessories



Compression fittings



Thermowells



Extension cable

Helium Projects Ltd

Projects House,
Rear of 6 St Lawrence Avenue, Worthing,
West Sussex, BN14 7JH

Tel: +44(0) 1903 211121 Fax: +44(0) 1903 211130

email: sales@helium.uk.net

Website: www.helium.uk.net